

F4 1000 R - R 1+1	
ENGINE	
Type	Four cylinder, 4 stroke, 16 valve
Timing system	"D.O.H.C", radial valve
Total displacement	998 cm ³ (60.8 cu. in.)
Compression ratio	13:1
Starting	Electric
Bore x stroke	76 mm x 55 mm (3.0 in. x 2.2 in.)
Max. horse power - r.p.m. (at the crankshaft)	130 Kw (174 HP) at 11900 - Lim. 13000 r.p.m.
Max. torque - r.p.m.	111 Nm (11.3 Kgm) at 10000 r.p.m.
Cooling system	Liquid cooled, water-oil heat exchanger
Engine management system	"Weber Marelli" 5SM ignition - injection integrated system; induction discharge electronic ignition, "Multipoint" electronic injection
Clutch	Wet, multi - disc
Gear Box	Cassette gearbox; six speed, constant mesh
Primary drive	50/79
Gear ratio	
First gear: Speed*	13/38 126,5 Km/h (78.5 mph) at 13000 r.p.m.
Second gear: Speed*	16/34 174,1 Km/h (108.1 mph) at 13000 r.p.m.
Third gear: Speed*	18/32 208,1 Km/h (129.2 mph) at 13000 r.p.m.
Fourth gear: Speed*	20/30 246,6 Km/h (153.1 mph) at 13000 r.p.m.
Fifth gear: Speed*	22/29 280,6 Km/h (174.2 mph) at 13000 r.p.m.
Sixth gear: Speed*	21/25 301,0 Km/h (187.0 mph) at 13000 r.p.m.
Final velocity ratio	15x40
ELECTRICAL EQUIPMENT	
Voltage	12V
Alternator	650 W at 5000 r.p.m.
Battery	12V - 9 Ah
DIMENSIONS AND WEIGHT	
Wheelbase	1408 mm (55.40 in.)
Overall length	2007 mm (79.01 in.)
Overall width	685 mm (26.97 in.)
Saddle height	810 mm (31.87 in.)
Min. ground clearance	130 mm (5.12 in.)
Trail	103,8 mm (4.08 in.)
Dry weight	F4 1000 R: 192 Kg (423.3 lb) - F4 1000 R 1+1: 193 Kg (425.5 lb)
Fuel tank capacity	21 l (5.54 U.S. gal.) - reserve fuel: 4 l (1.05 U.S. gal.)
PERFORMANCE	
Maximum speed*	301,0 Km/h (187.0 mph)
FRAME	
Type	CrMo Steel tubular trellis (TIG welded)
Rear swing arm pivot plates: material	Aluminium alloy
FRONT SUSPENSION	
Type	"UPSIDE - DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload adjustment
Rod dia.	50 mm (1.97 in.) with carbonitriding treatment
Travel on leg axis	129 mm (5.07 in.)
REAR SUSPENSION	
Type	Progressive, single shock absorber with rebound and compression (High speed / Low speed) damping and spring preload (hydraulic control)
Single sided swing arm: materiale	Aluminium alloy
Wheel travel	120 mm (4.72 in.)
BRAKE	
Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking band and aluminum flange
Front brake caliper	Radial-type with 4 pistons - Ø 34 mm (Ø 1.34 in.)
Rear brake	Single steel disc with Ø 210 mm (Ø 8.27 in.) diameter
Rear brake caliper	With 4 pistons - Ø 25,4 mm (Ø 1.00 in.)
RIM	
Front: Material / size	Forged aluminium alloy 3.50 " x 17 "
Rear: Material / size	Forged aluminium alloy 6.00 " x 17 "
TYRES	
Front	120/70 - ZR 17 (58W)
Rear	190/55 - ZR 17 (75 W)
FAIRING	
Material	Thermoplastic

* = Top speed attained on closed course.

MV Agusta Motor S.p.A. is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.